



# Calculation of Relative Uncertainty When Measuring Physical Constants: CODATA Technique Vs Information Method

Boris Menin<sup>1\*</sup>

<sup>1</sup>Mechanical and Refrigeration Consultation, Energy Efficiency, Beer-Sheba, 8464209, Israel.

## Author's contribution

The sole author designed, analysed, interpreted and prepared the manuscript.

## Article Information

DOI: 10.9734/PSIJ/2019/v22i430136

### Editor(s):

- (1) Professor. Bheemappa Suresha, Department of Mechanical Engineering, The National Institute of Engineering, Mysuru, India.  
(2) Dr. Christian Brosseau, Distinguished Professor, Department of Physics, Université de Bretagne Occidentale, France.

### Reviewers:

- (1) Francisco Bulnes, Tecnológico de Estudios Superiores de Chalco, Mexico.  
(2) Orchidea Maria Lecian, Sapienza University of Rome, Italy.  
(3) Chukwuemeka Ifegwu Eke, University of Abuja, Nigeria.  
(4) Pasupuleti Venkata Siva Kumar, Vallurupalli Nageswara Rao Vignana Jyothi Institute of Engineering and Technology, India.  
(5) Branko Vuković, University of Osijek, Croatia.  
Complete Peer review History: <http://www.sdiarticle3.com/review-history/50145>

Original Research Article

Received 04 May 2019  
Accepted 15 July 2019  
Published 23 July 2019

## ABSTRACT

**Aims:** To analyze the results of measurements of the Boltzmann, gravitational and Planck constants using a theoretically sound information approach in comparison with the CODATA technique.

**Place and Duration of Study:** Beer-Sheba, between January 2019 and May 2019.

**Methodology:** Using the concepts of information theory, the amount of information contained in the measurement model of a physical constant is calculated. This allows us to find the value of the comparative uncertainty proposed by Brillouin, and the achievable value of the relative uncertainty, taking into account the basic SI values used on each test bench when measuring physical constants.

**Results:** An unsolved question was to find the amount of information contained in the model of the measurement of a physical constant, which can be converted to the value of the achievable absolute uncertainty. This value now has an exact analytical formula. It is notoriously difficult to study the consistency of the measurement results of physical constants, but the proposed mathematical tool, developed using the concepts of information theory, allow us to simplify the analysis completely.

\*Corresponding author: E-mail: [meninbm@gmail.com](mailto:meninbm@gmail.com);

**Conclusion:** The information method leads to an intuitive and logically justified calculation of the relative uncertainty, which is compatible with the current practice of CODATA. This allows you to identify the threshold discrepancy between the model and the object under study. Proof of this is the calculation of the achievable value of the relative uncertainty when measuring the Boltzmann, gravitational and Planck constants. The proposed information-oriented method for calculating the relative uncertainty in measuring physical constants represents a new tool when formulating a modernized SI.

*Keywords: Boltzmann; gravitational and planck constants; CODATA; information theory; least squares correction; relative uncertainty.*

## 1. INTRODUCTION

The Committee's decision [1], seemingly so far from the consciousness and understanding of the majority of the 7.5 billion population of the Earth, opened a new era not only in measurement theory and metrology but also in all areas of human life. Over the last decade, thanks to huge investments, unique test benches, advanced mathematical methods, super-powerful computers and accumulated knowledge, the modification of the International system of units (SI) has become possible. It lies in the fact that four new definitions and four fixed numerical values of the basic constants have been established [1]. In this case, the uncertainty, necessarily associated with the data used, is discarded, and the value is assumed to be exact by agreement.

The process of fixing the value of the constant is carried out using the method of least squares correction (LSA). There is no published evidence that the latest adjustments can be considered equivalent, therefore, CODATA can only be trusted for the correctness of their work [2].

The LSA method is aimed at checking the consistency of the results, and for this, the initial experimental values are "corrected," that is, changed to optimize the final dispersion of the set. However, in these cases, the initial values are adjusted. This shortcoming is not available to the scientific community because the adjustments are not presented in CODATA publications.

The purpose of this article is to point out some features inherent in the approved CODATA method for calculating the value of the constants and their relative uncertainty. A positive discussion of this becomes important in view of the implementation of the revision of the International System of Measurement Units (SI) in 2019. The existing statistical features of the

CODATA method, along with the mandatory discussion and formulation of an expert opinion, may still raise doubts about the complexity and possible subjectivity of the tools used. The application of the LSA method and its influence on the decisions made by CODATA causes some skepticism. Don't forget the joke: statistics is one form of lies.

Unlike the accepted CODATA procedure for processing the results of experiments using LSA, we propose a new procedure for finding the recommended value of relative uncertainty, which simulates the results using the comparative uncertainty proposed by Brillouin and takes into account the basic SI values implemented on each test bench when measuring physical constants.

## 2. PROVISIONS AND SOME FORMULAS RELATED TO THE INFORMATION METHODS

Background premises and evidence are presented in previously published works [3-6]. Below, in a condensed form, the data necessary for subsequent reasoning and analysis of the results of measurements of physical constants are given.

The total number of the dimensionless criteria  $\mu_{SI}$  in SI equals

$$\mu_{SI} = 38,265 \quad (1)$$

SI is a set of dimensional quantities, base and derived, used for descriptions of different classes of phenomena (*CoP*), which depend on seven base quantities: meter, the length  $L$ ; kilogram, the mass  $M$ ; second, the time  $T$ ; kelvin, the thermodynamic temperature  $\theta$ ; ampere, the electrical current  $I$ ; mole, the amount of substance  $F$ ; candela, the luminous intensity  $J$  [7]. For example, when measuring the gravitational

constant by electromechanical methods, the basis {the length  $L$ , weight  $M$ , time  $T$ , electrical current  $I$ } is used, i.e.,  $CoP_{SI} \equiv LMTI$ .

The dimensionless measurement absolute uncertainty  $\Delta u$  of the dimensionless quantity  $u$  with a changed interval  $S$  can be calculated

$$\Delta u = S \cdot (z' - \beta') / \mu_{SI} + (z'' - \beta'') / (z' - \beta'), \quad (2)$$

where  $\beta'$  is the number of the base quantities of the chosen  $CoP$ ,  $z'$  is the total number of the dimensional quantities of the chosen  $CoP$ ,  $z''$  is a given number of the dimensional physical quantities recorded in the model,  $\beta''$  is the number of the base quantities recorded in the model,  $\varepsilon$  is the comparative uncertainty suggested by Brillouin [8],  $\varepsilon = \Delta u / S$ .

Equation (2) sets an ultimate limit on the accuracy of measuring a physical constant, which cannot be overcome by any measuring instruments, perfect mathematical methods, and using unique materials or software. This limit already exists before performing any calculations or implementing algorithms on a computer. Its value depends on the class of the phenomenon and the number of quantities taken into account.

The information-oriented method can be applied for measurements of *any dimensional or dimensionless physical constant* because the relative and comparative uncertainties of the dimensional quantity  $U$  and the dimensionless quantity  $u$  are equal:

$$\begin{aligned} \Delta U / S^* &= (\Delta U / a) / (S^* \cdot a) = (\Delta U / S) \\ (r/R) &= (\Delta U / U) / (\Delta u / u) = \Delta U / U \cdot (U/a) = 1 \quad (3) \end{aligned}$$

where  $\Delta u$  is the total absolute uncertainty in determining the dimensionless quantity  $u$ ;  $S^*$  and  $\Delta U$  are dimensional quantities (respectively, the range of variations and the total absolute uncertainty in determining the dimensional quantity  $U$ );  $a$  is the dimensional scale parameter with the same dimension as that of  $U$  and  $S^*$ ;  $r$  is the relative uncertainty of the dimensional quantity  $U$ ; and  $R$  is the relative uncertainty of the dimensionless quantity  $u$ .

Taking into account (2), one can verify conditions for calculating the minimum comparative uncertainty for a particular  $CoP$ :

$$(z' - \beta')^2 / \mu_{SI} = (z'' - \beta''). \quad (4)$$

According to (4), it is possible to check (Table 1) the optimal number of quantities in the model and the achievable comparative uncertainties recommended in the framework of the information method, as well as the  $CoP$  commonly used when measuring the Boltzmann, gravitational and Planck constants:

**Table 1. Comparative uncertainties and recommended number of dimensionless criteria**

$CoP_{SI}$	Comparative uncertainty	Recommended number of criteria
$LMT$	0.0048	$0.2 < 1$
$LMTF$	0.0146	$\cong 2$
$LMTI$	0.0245	$\cong 6$
$LMT\theta F$	0.1331	$\cong 169$
$LMT\theta I$	0.2220	$\cong 471$

It should be noted that the comparative uncertainty and the recommended number of values in the model are different and depend to the choice of  $CoP$ . From the data in Table 1, it can be seen that  $LMT$  and  $LMTF$  are not recommended for use in measurements of *physical constants* because there are very few criteria that can be used in the model. This causes a situation where an increase in the number of variables/criteria taken into account leads to an increase in experimental comparative uncertainty that can be achieved, which is much more than the recommended. Consequently, the discrepancy between the model and the really emerging process of measuring a physical constant increases.

An objective assessment of the achieved accuracy of measuring a physical constant, within the framework of the information approach, is confirmed using two metrics, denoted as  $IARU$  (information approach with relative uncertainty) and  $IACU$  (information approach with comparative uncertainty). In  $IARU$ , the interval of change of the physical constant  $S$  is calculated as the difference between the maximum and minimum values of the physical constant measured by various research groups in recent years. This is due to the need to consider the appearance of each experimental result in a given range as an independent event. In this case, knowing the comparative uncertainty inherent in the chosen class of phenomena, the recommended relative uncertainty is calculated. Its value, in turn, is compared with the relative uncertainty of each published study. (4)

For *IACU*, *S* is calculated in accordance with the technical limitations of measurement devices [8]. In this case, the standard uncertainty calculated in the experiment when measuring a physical constant is taken as the possible interval for the placement of its true value. The experimental absolute uncertainty is calculated by multiplying the value of the fundamental physical constant and its relative uncertainty achieved in each experiment. The achieved experimental comparative uncertainty of each published study is calculated by dividing the experimental absolute uncertainty by the standard uncertainty. Then, the experimentally calculated comparative uncertainty is compared with the selected comparative uncertainty (Table 1), which is inherent in the model describing the measurement of the fundamental constant.

### 3. ANALYZING RESULTS OF MEASURING THE BOLTZMANN, GRAVITATIONAL AND PLANCK CONSTANTS

A detailed analysis of the measurement of the Boltzmann, gravitational and Planck constants from the positions of *IARU* and *IACU* is presented in [4-6]. Methods and results with data on the values of physical constants, relative measurement uncertainties and standard uncertainties, published in scientific journals during 2000–2018 and confirmed by CODATA, were taken into account. Below, we present a summary of these studies (Tables 1, 2, 3), taking into account the application of *IARU*.

From the data presented in Tables 2–4, you can simply draw the following obvious conclusions.

Impressive advances in measuring physical constants have been achieved using DCGT for *k*. This is because of the significant difference in the magnitude of the comparative uncertainties between  $CoP_{SI} \equiv LMT\theta F$  (AGT – 0.1331) and  $CoP_{SI} \equiv LMT\theta I$  (DCGT – 0.2220). The only concern is that the experimental relative uncertainty is less than the relative uncertainty theoretically calculated (Table 2), which contradicts the information method. Therefore, a researcher using DCGT needs to recheck everything, if possible, and within the framework of the information approach—necessarily, potential sources of uncertainty.

- KB for *h*. This is because there is a twofold difference between the comparative uncertainties for  $CoP_{SI} \equiv LMTF$  (XRCD – 0.0146) and  $CoP_{SI} \equiv$

*LMTI* (KB – 0.0245) and almost equal placement interval of *h*.

- Electromechanical methods for *G*. This is due to the huge difference in comparative uncertainties between  $CoP_{SI} \equiv LMT$  ( $\epsilon_{LMT} = 0.0048$ ) and  $CoP_{SI} \equiv LMTI$  ( $\epsilon_{LMTI} = 0.0245$ ) and the closeness of the achieved lowest experimental value of relative uncertainty ( $1.2 \cdot 10^{-5}$ ) to the recommended one ( $6.3 \cdot 10^{-6}$ ). That is why further and detailed research of the current electromechanical methods should be continued.

Within the framework of the information method, several methods seem limited for future improvement:

- DBT ( $CoP_{SI} \equiv LMT\theta F$ ) for *k* in terms of the possibility of achieving higher accuracy. This is because the values of relative uncertainty, theoretically calculated and achieved in the experiment, are very close ( $2.1 \cdot 10^{-5}$  and  $2.4 \cdot 10^{-5}$ ).

- AGT ( $CoP_{SI} \equiv LMT\theta F$ ) for *k*. Given the fact that the interval of the possible placement of *k* for the AGT method ( $2.4 \cdot 10^{-29} \text{ m}^2 \text{ kg}/(\text{s}^2 \text{ K})$ ) is the smallest compared with other methods, it is difficult to expect any achievements in increasing its accuracy.

- Mechanistic methods ( $CoP_{SI} \equiv LMT$ ) for *G*. There are two reasons to stick to that point of view. The latest results for the relative uncertainty of the gravitational constant are very different from the relative uncertainty calculated by the *IARU* method (Table 4). Second, and, perhaps more importantly, in this case, the use of even one or several variables leads to an increase in the attainable experimental uncertainty, which is much more than the theoretically recommended value of the comparative uncertainty (Table 1).

To compare all the methods used, Table 5 was compiled. As shown in Table 5, despite the huge differences between the methods in order of magnitude of relative values according to  $CoP_{SI}$ , relative uncertainty according to  $CoP_{SI}$  (*IARU*)  $r_{SI}$ , and experimental minimum relative uncertainty  $r_{exp}$ , the ratio  $r_{exp}/r_{SI}$  varies in a rather small interval (0.9–3.0) compared with models V (mechanistic methods, gravitational constant) and VIII (XRCD, Planck constant). Consistency is a basic requirement for a new SI, but you may ask why V and VIII stand out?

We wonder if it arises straight from the application of the LSA method, or is it due to any

further culling of the data—including by CODATA [9]? In fact, this degree of consistency can exist simply due to the application of the LSA method and as a result of reducing the uncertainty of the measurement data. Perhaps the situation will change for the better if the new method of processing the results of measurements of physical constants is used in the CODATA technique [10].

However, there is another reason to explain this situation in the context of an information-oriented approach.

Already in the process of formulating the method of measuring the physical constant, there is an unremovable uncertainty, called comparative uncertainty, due to the number of variables and the qualitative set of base quantities in the model. It is not constant and changes depending

on the number of recorded base quantities. In addition, according to the calculations formulated within the framework of the presented approach, the use of *LMT* and *LMTF* is *not recommended* because the achievement of the theoretical value of comparative uncertainty in practice is impossible. This is because when using these *CoP*, numerous potential effects are not taken into account, and the recommended number of selected criteria is less than two. That is why, within the framework of the information-oriented method in contrast to the method adopted in CODATA, *it is inappropriate to establish only one value of relative uncertainty when measuring physical constants by various methods*. This is explained by the fact that for models inherent in different *CoP*, there are different values of comparative uncertainties and a different number of quantities, which is recommended to choose.

**Table 2. Summarized data of the Boltzmann constant, *k***

Variable	AGT	DCGT	JNT	DBT
<i>CoP</i>	<i>LMTθF</i>	<i>LMTθI</i>	<i>LMTθI</i>	<i>LMTθF</i>
Comparative uncertainty according to <i>CoP<sub>SI</sub></i>	0.1331	0.2220	0.2220	0.1331
Possible observed range <i>S<sub>k</sub></i> of <i>k</i> placing, m <sup>2</sup> ·kg/(s <sup>2</sup> ·K)	2.4·10 <sup>-29</sup>	2.7·10 <sup>-29</sup>	9.2·10 <sup>-29</sup>	2.2·10 <sup>-27</sup>
Relative uncertainty according to <i>CoP<sub>SI</sub></i> , <i>r<sub>k</sub></i>	2.3·10 <sup>-7</sup>	4.3·10 <sup>-7</sup>	1.4·10 <sup>-6</sup>	2.1·10 <sup>-5</sup>
Achieved experimental lowest relative uncertainty, <i>r<sub>kexp</sub></i>	6.0·10 <sup>-7</sup>	3.7·10 <sup>-7</sup>	2.7·10 <sup>-6</sup>	2.4·10 <sup>-5</sup>
Ratio of <i>r<sub>kexp</sub></i> / <i>r<sub>k</sub></i>	2.6	0.9	1.9	1.1

**Table 3. Summarized data of the Planck constant, *h***

Variable	KB	XRCD
<i>CoP</i>	<i>LMTI</i>	<i>LMTF</i>
Comparative uncertainty according to <i>CoP<sub>SI</sub></i>	0.0245	0.0146
Possible observed range <i>S<sub>h</sub></i> of <i>h</i> placing, m <sup>2</sup> ·kg/s	1.2·10 <sup>-40</sup>	4.6·10 <sup>-41</sup>
Relative uncertainty according to <i>CoP<sub>SI</sub></i> ( <i>IARU</i> ), <i>r<sub>k</sub></i>	4.5·10 <sup>-9</sup>	1.0·10 <sup>-9</sup>
Achieved experimental lowest relative uncertainty, <i>r<sub>kexp</sub></i>	1.3·10 <sup>-8</sup>	9.1·10 <sup>-9</sup>
Ratio of <i>r<sub>kexp</sub></i> / <i>r<sub>k</sub></i>	3.0	9.1

**Table 4. Summarized data of the gravitational constant, *G***

Variable	Mechanistic methods	Electromechanical methods
<i>CoP</i>	<i>LMT</i>	<i>LMTI</i>
Comparative uncertainty according to <i>CoP<sub>SI</sub></i>	0.0048	0.0245
Possible observed range <i>S<sub>G</sub></i> of <i>G</i> placing, m <sup>3</sup> /(kg·s <sup>2</sup> )	2.1·10 <sup>-14</sup>	1.7·10 <sup>-14</sup>
Relative uncertainty according to <i>CoP<sub>SI</sub></i> ( <i>IARU</i> ), <i>r<sub>G</sub></i>	1.5·10 <sup>-6</sup>	6.3·10 <sup>-6</sup>
Achieved experimental lowest relative uncertainty, <i>r<sub>Gexp</sub></i>	1.9·10 <sup>-5</sup>	1.2·10 <sup>-5</sup>
Ratio of <i>r<sub>Gexp</sub></i> / <i>r<sub>G</sub></i>	12.7	1.9

**Table 5. Comparison data of measuring the Boltzmann, gravitational and Planck constants**

Fundamental constant Variable / Method	Boltzmann constant				Gravitational constant		Planck constant	
	AGT	DCGT	JNT	DBT	Mechanistic methods	Electro- mechanical methods	KB	XRCD
	I	II	III	IV	V	VI	VII	VIII
<b>CoP</b>	<b>LMT<math>\theta</math>F</b>	<b>LMT<math>\theta</math>I</b>	<b>LMT<math>\theta</math>I</b>	<b>LMT<math>\theta</math>F</b>	<b>LMT</b>	<b>LMTI</b>	<b>LMTI</b>	<b>LMTF</b>
Comparative uncertainty according to $CoP_{SI}$	0.1331	0.2220	0.2220	0.1331	0.0048	0.0245	0.0245	0.0146
Relative uncertainty according to $CoP_{SI}$ (IARU), $r_{SI}$	$2.3 \cdot 10^{-7}$	$4.3 \cdot 10^{-7}$	$1.4 \cdot 10^{-6}$	$2.1 \cdot 10^{-5}$	$1.5 \cdot 10^{-6}$	$6.3 \cdot 10^{-6}$	$4.5 \cdot 10^{-9}$	$1.0 \cdot 10^{-9}$
Achieved experimental lowest relative uncertainty, $r_{exp}$	$6.0 \cdot 10^{-7}$	$3.7 \cdot 10^{-7}$	$2.7 \cdot 10^{-6}$	$2.4 \cdot 10^{-5}$	$1.9 \cdot 10^{-5}$	$1.2 \cdot 10^{-5}$	$1.3 \cdot 10^{-8}$	$9.1 \cdot 10^{-9}$
Ratio of $r_{exp}/r_{SI}$	2.6	0.9	1.9	1.1	12.7	1.9	3.0	9.1

#### 4. CONCLUDING REMARKS

An unsolved question was to find the amount of information contained in the model of the measurement of a physical constant, which can be converted to the value of the achievable absolute uncertainty. This value now has an exact analytical formula. It is notoriously difficult to study the consistency of the measurement results of physical constants, but the proposed mathematical tool, developed using the concepts of information theory, allowed us to simplify the analysis completely.

It is obvious from the analyzed data that an information approach is a universal tool for verifying accuracy and recommended values of relative uncertainties. The information-oriented method does not depend on the subjective judgment of the expert and is free from any inaccuracies, weighting factors inherent in statistical methods and accessible to all (meaning no hierarchy). It is very easy to use; it is available even to students, user understandable and it does not require complex calculations and is performed in a short time. It is not unimportant that this method is theoretically justified and conceptually correct.

The approach implements a simple and reliable way of formulating a model with the optimal number of quantities taken into account. Thus, the duration of the experiments and their cost could be significantly reduced.

From the point of view of the author, the information method leads to a theoretically proven, intuitive, and logically sound calculation of relative uncertainty, which is compatible with modern CODATA practice. This allows you to identify the threshold discrepancy between the model and the object under study. Proof of this is the calculation of the achievable value of the relative uncertainty when measuring the Boltzmann, gravitational and Planck constants.

The author does not want to look like a person who automatically criticizes the CODATA methodology. Of course, recent years have been marked by great achievements in measuring fundamental constants with reduced uncertainty, which led to outstanding results. However, one should keep in mind the possible "enthusiasm" of CODATA scientists in search of the threshold value of uncertainty. Therefore, the information approach can serve as a theoretically justified tool for confirming certain values of relative uncertainties.

Based on the foregoing, it seems correct to assume that the proposed information-oriented method for calculating the relative uncertainty in measuring physical constants represents a new tool when formulating a modernized SI.

In the end, the author expresses the hope that the proposed method, along with the current version of SI, can be labeled as "for all times, for all people."

#### CONSENT

It is not applicable.

#### ETHICAL APPROVAL

1. I, the alone corresponding author, am authorized to submit this manuscript.
2. Submission of the manuscript represent that the manuscript has not been published previously and is not considered for publication elsewhere.
3. The manuscript, or any part thereof, is in no way a violation of any existing original or derivative copyright.
4. The manuscript contains nothing obscene, indecent, objectionable or libelous.

#### COMPETING INTERESTS

Author has declared that no competing interests exist.

#### REFERENCES

1. Schlaminger S, Abbott P, Kubarych Z, Jarrett D, Elmquist RE. The units for mass, voltage, resistance, and current in the SI. *IEEE Instrum Meas.* 2019;22(3):1-16. (Accessed 5 June 2019) DOI: 10.1109/MIM.2019.8716269.
2. Pavese F. The new SI and the CODATA recommended values of the fundamental constants 2017 compared with 2014. 2018;1-11. (Accessed 5 June 2019) Available: <https://arxiv.org/ftp/arxiv/papers/1512/1512.03668.pdf>.
3. Menin B. Simplest method for calculating the lowest achievable uncertainty of model at measurements of fundamental physical constants. *Journal of Applied Mathematics and Physics.* 2017;5(11):2162-71. (Accessed 5 June 2019) Available: <https://goo.gl/XcCCX5>.

4. Menin B. The Boltzmann constant: Evaluation of measurement relative uncertainty using the information approach. *Journal of Applied Mathematics and Physics*. 2019;7(3):486-504.  
(Accessed 5 June 2019)  
Available: [10.4236/jamp.2019.73035](http://10.4236/jamp.2019.73035).
5. Menin B. Precise measurements of the gravitational constant: Revaluation by the information approach. *Journal of Applied Mathematics and Physics*. 2019;7(6):1272-1288.  
(Accessed 29 June 2019)  
Available:  
[http://file.scirp.org/pdf/JAMP\\_2019062614403787.pdf](http://file.scirp.org/pdf/JAMP_2019062614403787.pdf).
6. Menin B. Progress in reducing the uncertainty of measurement of Planck's constant in terms of the information approach. *Physical Science International Journal*. 2019;21(2):1-11.  
(Accessed: 5 June 2019)  
Available:<http://www.journalpsij.com/index.php/PSIJ/article/view/30104/56478>.
7. NIST Special Publication 330 (SP330). *The International System of Units (SI)*; 2008.  
(Accessed 5 June 2019)  
Available:<http://physics.nist.gov/Pubs/SP330/sp330.pdf>.
8. Brillouin L. *Science and information theory*. New York: Dover; 2004.
9. Mohr PJ, Newell DB, Taylor BN, Tiesinga E. Data and analysis for the CODATA 2017 special fundamental constants adjustment for the revision of the SI. *Metrologia*. 2018;55(1):125-46.  
(Accessed 5 June 2019)  
Available:  
<https://iopscience.iop.org/article/10.1088/1681-7575/aa99bc/pdf>.
10. Merktas C, Toman B, Possolo A, Schlaminger S. Shades of dark uncertainty and consensus value for the Newtonian constant of gravitation. 2019;1-39.  
(Accessed: 5 June 2019)  
Available: [arXiv:1905.09551v1](https://arxiv.org/abs/1905.09551v1) [physics.data-an] 23 May 2019.

© 2019 Menin; This is an Open Access article distributed under the terms of the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/4.0>), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

*Peer-review history:*  
*The peer review history for this paper can be accessed here:*  
<http://www.sdiarticle3.com/review-history/50145>